

US007902819B2

(12) United States Patent Hohman et al.

US 7,902,819 B2

(45) **Date of Patent:**

(10) **Patent No.:**

Mar. 8, 2011

(54) RIVET ROTATING EDDY CURRENT PROBE

(75) Inventors: Edward Hohman, Mansfield, TX (US);

Dennis Roach, Albuquerque, NM (US);

Rirk Rackow, Albuquerque, NM (US);

Phil Walkington, Albuquerque, NM

(US)

(73) Assignee: Textron Innovations, Inc., Providence,

RI (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 558 days.

(21) Appl. No.: 11/664,665

(22) PCT Filed: Oct. 7, 2005

(86) PCT No.: PCT/US2005/036070

§ 371 (c)(1),

(2), (4) Date: Dec. 19, 2007

(87) PCT Pub. No.: WO2007/015705

PCT Pub. Date: Feb. 8, 2007

(65) Prior Publication Data

US 2008/0211493 A1 Sep. 4, 2008

Related U.S. Application Data

(60) Provisional application No. 60/617,311, filed on Oct. 8, 2004.

(51) Int. Cl. G01N 27/82 (2006.01) G01R 33/12 (2006.01)

(52) **U.S. Cl.** **324/240**; 324/242; 324/228

(56) References Cited

U.S. PATENT DOCUMENTS

5,648,721	A	7/1997	Wincheski et al.	
7,301,335	B2 *	11/2007	Sun et al 324/240	
7,352,176	B1 *	4/2008	Roach et al 324/240	
2004/0051525	A1	3/2004	Hatcher et al.	

OTHER PUBLICATIONS

Canadian Office Action dated Jul. 6, 2009 from CA Application 2,580,278.

Response dated Dec. 31, 2009 from CA Application 2,580,278. Chinese First Office dated May 25, 2009 from CA Application 2005800334800

Response dated Jun. 26, 2009 from CN Application 2005800334800. Chinese Second Office Action dated Dec. 11, 2009 from CN Application 2005800334800.

Carlon 2003-8000-54800. European Search Report dated Dec. 18, 2009 from EP Application 05858442.6.

U.S. Appl. No. 11/502,085, filed Aug. 10, 2006.

European Office Action dated Feb. 8, 2010 from EP Application 05858442.6.

* cited by examiner

Primary Examiner — Kenneth J Whittington (74) Attorney, Agent, or Firm — James E. Walton; Richard G. Eldredge

(57) ABSTRACT

An eddy current probe adapted for detecting cracks in material directly beneath a raised-head fastener is disclosed. The probe comprises an eddy current coil and a support for carrying the coil in an orientation suitable for introducing eddy currents into material directly beneath a raised-head fastener.

19 Claims, 3 Drawing Sheets

